



Material
Housing: PA66, UL 94V-0
Screw: M2 Steel, Zn plated
Clamp: Brass, Ni plated
Cage: Brass, Ni plated
Fix screws: M2.5 Steel, Zn plated

Electrical
Rated voltage: 300V
Rated current: 8A
Contact Resistance: 20 mΩ
Insulation resistance: 500MΩ/DC500V
Withstand voltage: AC2000V / 1 min
Wire Range: 28 ~ 16AWG 1.5mm²

Mechanical
Temp. Range: -40 °C ~ +105 °C
Strip length: 6 ~ 7mm
Torque: 0.2Nm(1.77Lbin)

Order Information

L-KLS2- EDGFM -3.81-XXP-4 S 00

RoHS
Terminal Block
Pitch
No.: of Pole
Color: 4- Green
Screw: S-Slot Screw C-Crass Screw
Product Code: 00 ~ 99

GENERAL TOLERANCE	ANGLE TOLERANCE	Description:
X. ±0.60	X. ±5°	Pluggable Terminal block 3.81MM
.X ±0.38	.X ±3°	
.XX ±0.25	.XX ±2°	KLS P/N: KLS2-EDGFM-3.81-XXP-4S-00
Draw by 2015-09-01	PROJECTION	NingBo KLS ELECTRONIC CO.,L TD.
Check by 2015-09-15	UNITS mm	
SCALE	SHEET SIZE A4	