



Material
 Housing: PA66, UL94V-0
 Screws: M3 Steel, Zn plated
 Cage: Brass, Zn plated
 Clamp: Phosphor bronze, Ni Plated

Electrical
 Rated voltage: 300V
 Rated current: 10A
 Contact Resistance: 20 mΩ
 Insulation resistance: 5000MΩ/DC1000V
 Wire range: 28-14 AWG 2.5mm²
 Withstand voltage: AC2000V / 1min

Mechanical
 Torque: 0.5NM(4.5Lb.in)
 Steip length: 7-8mm
 Temp. Range: -40 °C ~ +105 °C

Order Information

L-KLS2-EDKP-5.00-XXP-4S00
 RoHS-
 Terminal Block
 Pitch
 No.: of Pole
 Color: 4- Green
 Screw: S-Slot Screw C-Cross Screw
 Product Code: 00~99

GENERAL TOLERANCE		ANGLE TOLERANCE		Description:
X. ±0.60		X. ±5°		Pluggable Terminal Block 5.00MM
.X ±0.38		.X ±3°		
.XX ±0.25		.XX ±2°		
Draw by	2015-09-01	PROJECTION		KLS P/N: KLS2-EDKP-5.00-XXP-4S-00
Check by	2015-09-15	UNITS	mm	NingBo KLS ELECTRONIC CO.,L TD.
SCALE		SHEET SIZE	A4	