



Material
Housing: PA66, UL94V-0
Screws: M3 Steel, Zn plated
Pin header: Brass, Tin plated
Cage: Brass, Tin plated
Nut: Brass

Electrical
Rated voltage: 300V
Rated current: 15A
Contact Resistance: 20 m Ω
Insulation resistance: 500M Ω /DC500V
Wire range: 28-14 AWG 2.5mm²
Withstand voltage: AC2000V / 1 min

Mechanical
Torque: 0.5NM(4.5Lb.in)
Steip length: 7-8mm
Temp. Range: -40 °C ~ + 105 °C

Order Information
L-KLS2- UNKM -5.08-XXP-4 S 00

RoHS
Terminal Block
Pitch
No.: of Pole
Color: 4- Green
Screw: S-Slot Screw C-Crass Screw
Product Code: 00~99

GENERAL TOLERANCE		ANGLE TOLERANCE		Description:	
X. ± 0.60		X. $\pm 5^\circ$		Pluggable Terminal Block 5.08MM	
.X ± 0.38		.X $\pm 3^\circ$			
.XX ± 0.25		.XX $\pm 2^\circ$			
Draw by	2015-09-01	PROJECTION		KLS P/N:	KLS2-UNKM-5.08-XXP-4S-00
Check by	2015-09-15	UNITS	mm		NingBo KLS ELECTRONIC CO.,L TD.
SCALE		SHEET SIZE	A4		